



**Kingfisher
Lighting**

Part of the **LUCCECO** group of companies

Datasheet

NAVAR Pro Cantilever




Specification Text

The NAVAR Pro shall be manufactured from high-pressure die-cast aluminium and powder coated with a RAL 7016 Anthracite Grey Marine Grade Finish. Its power outputs shall range to 315W. The luminaire shall deliver up to 139 lm/W with luminaire lumen outputs ranging from 15,307 - 35,638. The NAVAR Pro shall have a range of different optics to suit open areas and streets as well as a fully programmable DALI driver. Available in 2700K or 4000K, the luminaire shall be IK10 and IP66 rated.

Specification

Weight:	26.2 - 27.7 kg
Windage:	0.18 m ²
Material:	Die-cast Aluminium
Paint Finish:	RAL7016 Anthracite Grey
Embodied Carbon:	387 kg CO ₂ e

Optics



Forward Throw Optic 70°
Open areas, perimeter lighting

Product Description

Sleek with outstanding performance, the NAVAR Pro is our circular amenity luminaire guaranteed to bring a modern aesthetic to your site.

Key Features

- 118.0W - 315.0W
- 15,307 - 35,638 Luminaire Lumens
- Efficacy up to 139.0 lm/W
- 2700K, 4000K, CRI>70
- IP66 & IK10
- Lifetime 100,000, L80
- Fully Programmable DALI Driver
- Colour Temperature Opportunities
- Marine Grade Finish



**Kingfisher
Lighting**

Part of the **LUCCECO** group of companies

IP66	IK10	100,000 hrs LIFETIME	5 YEARS WARRANTY	
	2700K	4000K		



Circular Economy Score

0 to 0.05	Very poor circular economy performance
0.5 to 1.5	Some circular economy functionality
1.5 to 2.5	Definite/substantial progress to circularity
2.5 to 4.0	Excellent circularity

Other Options Available

Contact for further details


- Colour Temperature Options

Mounting Options

- Cantilever Bracket 76mm

Body Type	A	B	C	D
Standard	935	935	1049	76

All measurements in mm



Code	Power	Luminaire Lumens	Drive Current	Inrush Current A pk	Optic	CCT(K)	IP	IK	Weight kg	Driver Included	Driver Type
NAVPRO-CANT-FW70-120D	118.0	16,489	300	53 + 53	Asymmetric Forward Throw Optic 70°	4000	IP66	IK10	26.2	Yes	DALI
NAVPRO-CANT-FW70-120D27K	118.0	15,307	300	53 + 53		2700	IP66	IK10	26.2	Yes	DALI
NAVPRO-CANT-FW70-190D	191.0	24,857	475	53 + 53		4000	IP66	IK10	27.7	Yes	DALI
NAVPRO-CANT-FW70-190D27K	191.0	23,184	475	53 + 53		2700	IP66	IK10	27.7	Yes	DALI
NAVPRO-CANT-FW70-315D	315.0	35,638	750	53 + 53		4000	IP66	IK10	27.7	Yes	DALI
NAVPRO-CANT-FW70-315D27K	315.0	33,696	750	53 + 53		2700	IP66	IK10	27.7	Yes	DALI