



# Kingfisher Lighting

Part of the LUCECO group of companies

## Datasheet



# ALFRESCO Urban


### Specification Text

The ALFRESCO Urban shall be manufactured from high-pressure die-cast aluminium. It shall have an efficacy of up to 107.0 lm/W and will be capable of producing up to 2,147 luminaire lumens at 4000K with a CRI >80. The wall mounted luminaire provides a diffused aesthetic and comes with photocell, motion sensor and emergency capabilities. It shall have asymmetric optics and is rated at IP65 and IK08.

### Specification

Weight: 2.5 kg  
Material: Die-cast Aluminium  
Paint Finish: RAL7016 Anthracite Grey

### Optics



Asymmetrical 180x90°

### Product Description

Simple and classic, ALFRESCO Urban was created to suit many applications. Available with photocell and microwave sensor options, it's the perfect all rounder.



Part of the LUCECO group of companies

### Key Features

- 20.0W
- 1,183 - 2,147 Luminaire Lumens
- Efficacy up to 107.0 lm/W
- 2700K, 4000K, CRI>80
- IP65 & IK08
- Lifetime 50,000, L70
- Motion Sensor
- Emergency Compatible
- Photocell Options

|      |      |                    |                     |                  |  |
|------|------|--------------------|---------------------|------------------|--|
| IP65 | IK08 | Colour Temperature | 50,000 hrs LIFETIME | 5 YEARS WARRANTY |  |
|------|------|--------------------|---------------------|------------------|--|

|    |     |       |       |
|----|-----|-------|-------|
| EM | PEC | 2700K | 4000K |
|----|-----|-------|-------|

## Other Options Available

Contact for further details


- Colour Temperature Options
- Motion Sensor
- Emergency Options

| Body Type | A   | B   | C   |
|-----------|-----|-----|-----|
| Standard  | 340 | 340 | 105 |

All measurements in mm

## Mounting Options

- Wall Mount



| Code            | Power | Luminaire Lumens | Drive Current | Inrush Current A pk | Optic                   | CCT(K) | IP   | IK   | Weight kg | Driver Included | Driver Type |
|-----------------|-------|------------------|---------------|---------------------|-------------------------|--------|------|------|-----------|-----------------|-------------|
| ALFH20F         | 20.0  | 2,147            | 500           | 9.0                 | Asymmetrical<br>180x90° | 4000   | IP65 | IK08 | 2.5       | Yes             | Fixed       |
| ALFH20FPEC      | 20.0  | 2,147            | 500           | 9.0                 |                         | 4000   | IP65 | IK08 | 2.5       | Yes             | Fixed       |
| ALFH20FEM       | 20.0  | 2,147            | 500           | 9.0                 |                         | 4000   | IP65 | IK08 | 2.5       | Yes             | Fixed       |
| ALFH20FEMPEC    | 20.0  | 2,147            | 500           | 9.0                 |                         | 4000   | IP65 | IK08 | 2.5       | Yes             | Fixed       |
| ALFH20F27K      | 20.0  | 1,813            | 500           | 9.0                 |                         | 2700   | IP65 | IK08 | 2.5       | Yes             | Fixed       |
| ALFH20F27KPEC   | 20.0  | 1,813            | 500           | 9.0                 |                         | 2700   | IP65 | IK08 | 2.5       | Yes             | Fixed       |
| ALFH20F27KEM    | 20.0  | 1,813            | 500           | 9.0                 |                         | 2700   | IP65 | IK08 | 2.5       | Yes             | Fixed       |
| ALFH20F27KEMPEC | 20.0  | 1,813            | 500           | 9.0                 |                         | 2700   | IP65 | IK08 | 2.5       | Yes             | Fixed       |